How State Graphs, Memory, and Delegation Shape Autonomous Agents


Autonomous AI agents are no longer a lab curiosity. They can browse the web, book appointments, write code, and even negotiate with other agents. But building one that behaves reliably over time is harder than it looks. The core challenge is not just making a model that can "think" in a single step, but one that can remember what it has done, decide what to do next, and hand off tasks to other agents or tools without losing context. Three concepts sit at the heart of this: state graphs, memory, and delegation.

What a State Graph Is and Why It Matters

A state graph is a way to model the possible states an agent can be in and the transitions between them. Think of it as a map of the agent's journey. Each node represents a situation or a stage of a task, and each edge represents an action or an event that moves the agent from one stage to the next. For example, an agent booking a flight might have states like "awaiting departure city," "awaiting destination," "dates confirmed," "payment pending," and "booking complete." The edges are the actions the agent takes or the inputs it receives.

State graphs give an agent structure. Without one, an agent relies entirely on the language model's next-token prediction to figure out what to do. That works for simple questions but falls apart for multi-step tasks. The agent can get stuck in loops, forget where it is, or take an action that makes no sense because it has no sense of progress. A state graph acts as a guardrail. It limits the agent's choices to only those that are meaningful at the current point in the task. This is not about restricting intelligence but about providing a scaffold that intelligence can operate within safely.

In practice, state graphs are often defined as directed graphs, sometimes with probabilistic transitions, sometimes with deterministic ones. Developers can hand-craft them for known workflows, or the agent can build one dynamically as it discovers new steps. The trade-off is control versus flexibility. A hand-crafted graph is predictable and easy to debug, but brittle when the task changes. A dynamically built graph is adaptable, but can drift into undefined states if the underlying model is not well constrained.



Memory: The Agent's Long-Term Context

An agent's memory is not the same as a language model's context window. The context window is the immediate conversation history. It is finite and expensive to extend. Memory, in the agentic sense, refers to the ability to store, retrieve, and use information across sessions and tasks. This can be as simple as a key-value store of facts the agent has learned, or as complex as a vector database of past interactions that the agent can query for relevant context.


There are two broad types of memory that matter for autonomous agents: episodic and semantic. Episodic memory records specific events in time, such as "the user asked about flights to Tokyo on Tuesday." Semantic memory stores general knowledge, such as "the user prefers window seats." Both are necessary for a coherent agent. Without episodic memory, the agent cannot remember what it just did. Without semantic memory, it cannot learn from repeated interactions.

Memory also introduces a design tension. Storing everything makes retrieval slow and noisy. Storing too little makes the agent forgetful. A common approach is to use a hierarchy: a short-term buffer for the current task, a working memory for the session, and a long-term store for persistent knowledge. Each layer has a different retention policy and retrieval strategy. The agent must decide what to forget and what to keep, and that decision itself is a surprisingly subtle problem. Some systems use a second model to summarise and compress memories, while others rely on time-based decay or relevance scoring.

Delegation: When One Agent Is Not Enough

No single agent can be good at everything. Delegation is the mechanism by which an agent hands off a subtask to another agent or tool. This could be a specialised agent trained for a specific domain, a simple API call, or even a human-in-the-loop. The delegating agent needs to know what the subtask is, who can handle it, and how to interpret the result.

Delegation requires a shared language. The agents need to agree on a protocol for passing context and results. This is where state graphs and memory come back into play. The delegating agent's state graph includes a node for "waiting for result from delegate." It pauses there until the delegate returns. The delegate, in turn, may have its own state graph and memory. The delegating agent must also remember what it asked for, so it can interpret the reply and decide what to do next.



This pattern is common in multi-agent systems. One agent might be responsible for research, another for writing, and a third for fact-checking. The orchestrator delegates each step and collects results. But delegation is not only about other agents. It also applies to tools: a code execution environment, a search engine, a calculator. Each tool call is a form of delegation, and the same principles apply. The agent must track the delegation in its state graph and store the result in its memory for later use.

Putting It All Together

When state graphs, memory, and delegation work together, the agent becomes something more than a chatbot. It becomes a persistent, goal-directed system. It can pause a task, hand it off, resume it later, and remember what happened before. This is the architecture behind many of the autonomous AI agents being built today. Publications like futurestack.online regularly explore these patterns, offering detailed breakdowns of how engineers design and debug such systems in practice.

One common pitfall is treating memory as a dump. Developers sometimes store everything in a vector database and hope the retrieval is good enough. It rarely is. The agent ends up retrieving irrelevant context, which pollutes the state graph and causes wrong transitions. A better approach is to tie memory entries to specific states in the graph. When the agent enters a state, it knows which memories are relevant and can query them explicitly. This is closer to how a human works: when you are booking a flight, you do not think about your entire life history. You think about the trip.

Another pitfall is over-delegation. It is tempting to break every task into tiny subtasks and hand them off to specialised agents. But each delegation adds latency and risks miscommunication. The agent's state graph becomes a tangled mess of dependencies, and debugging a failure requires tracing through multiple agents. The best systems use delegation sparingly, only when the subtask genuinely requires a different capability or a different source of knowledge.

What This Means for Developers

If you are building an autonomous agent, start with the state graph. Map out the key states and transitions before you write any code. Then decide what memory each state needs. Then think about delegation as an extension of the graph, not as a separate concern. The graph is the skeleton. Memory is the flesh. Delegation is the nervous system that connects different parts of the organism.



There is no perfect architecture. Every choice involves trade-offs. A rigid state graph is safe but inflexible. A flexible graph is powerful but can behave unpredictably. A rich memory makes the agent smarter but slower. Delegation distributes work but introduces coupling. The art is in finding the right balance for your use case. The engineering community, including sites like futurestack.online, continues to share practical lessons from real deployments, and that collective knowledge is one of the best resources for anyone working in this space.

Autonomous agents are evolving fast. The ones that work reliably are not magic. They are carefully designed systems where state, memory, and delegation are treated as first-class components, not afterthoughts. Understanding these three concepts is the foundation for building agents that do not just answer questions but actually get things done.

Futurestack.online on social media Instagram