

A garage door that **shuts and reopens** is usually reacting to a mechanical or safety issue. The opener senses resistance, an interrupted sensor beam, incorrect travel limits, or an unbalanced door and reverses before the door can stay closed. This behavior keeps safe people, vehicles, and property, but it also means your garage door may not be safe to operate until the cause is found.

EM Garage Doors And Gate Service Inc

19629 Cantara St, Reseda, CA 91335

(818) 919-0785

<https://emgaragedoorsandgateservice.com/>

<https://maps.app.goo.gl/XujLWxA4pAQKARQT8>

34.2193569, -118.5613022

This guide describes the most common reasons an overhead garage door reverses, which checks are safe to perform yourself, and when professional **garage door repair** is the right decision. It also covers garage door repair cost and service considerations for homeowners in Los Angeles.

Why a Garage Door Closes Then Opens

Most modern systems use a **garage door opener** with programmed travel limits and automatic safety reversal. The opener observes the door while it moves down. If it senses unusual resistance or receives a signal that the safety beam is interrupted, it reverses the door.



The most frequent causes include dirty or misaligned **photo-eye sensors**, an obstruction along the **garage door tracks**, a door that is too heavy, or incorrect **travel-limit settings**. If the opener believes the door has reached the floor before it actually has, it may reverse. If it believes the door is hitting an object, it may also reopen.

A door that **reverses before touching the floor** often points to a sensor or travel-limit issue. A door that reaches the floor and then opens may have a force-setting problem, a damaged bottom seal, a binding track, or a door that is not properly balanced. The exact timing of the reversal is useful diagnostic information for a technician.

Common Reasons of This Garage Door Problem

Several parts can cause a garage door to reopen after closing:

- **Safety sensors:** Debris, sunlight, poor positioning, damaged lenses, or unstable wiring can interrupt the infrared beam.
- **Garage door spring:** A damaged or snapped spring cannot properly counterbalance the door, causing excess strain on the opener.
- **Garage door rollers:** Aged, cracked, or seized rollers can create resistance as the door travels downward.
- **Garage door cables:** Damaged or loose cables can cause the door to hang unevenly or jam in the tracks.

Other contributing issues include a damaged panel, a deteriorated weather seal, a poorly tensioned chain or belt, a malfunctioning wall control, or an opener that is close to the end of its service life. Do not presume that adjusting the opener is always the answer. A force adjustment can temporarily conceal a mechanical fault and may create a unsafe operating condition.

Misaligned or Interrupted Safety Sensors

Safety sensors are usually mounted near the bottom of each side of the door opening. They use **photo-eye units** to create an invisible beam across the threshold. If that beam is blocked while the door is closing, the opener activates the **garage door safety reversal** feature.

Inspect whether anything is in the **obstructed sensor path**. Boxes, tools, garbage containers, leaves, or even a vehicle parked too close to the opening can interfere with the beam. Wipe both sensor lenses with a gentle, dry cloth. Do not spray cleaner directly on the sensors.

Then, inspect **sensor alignment**. The sensors should be aimed straight at each other and be mounted at approximately the same height. A bump from a yard tool, vacuum, bicycle, or storage item can move one bracket. A **blinking sensor light** is often a sign that the beam is not being received correctly, although light patterns can change by opener brand.

Inspect the **sensor wiring** for obvious damage, loose connections, pinched areas, or corrosion. You can carefully adjust a sensor bracket if it is obviously tilted, but do not override or disconnect the safety system. A garage door should never be operated with its safety sensors defeated. If cleaning and proper adjustment do not solve the problem, a professional should test the sensors, wiring, and opener logic.

Track, Roller, and Obstruction Problems

Inspect the **garage door tracks** from the floor to the top of the opening. Look for a **bent track**, loose mounting hardware, dents, gaps, or debris. Tracks guide the rollers and are not intended to be severely reshaped by homeowners. Attempting to straighten a severely damaged track can let stored tension escape or cause the door to fall.

Examine the **garage door rollers** for cracks, excessive wobbling, flat spots, or signs that a roller is coming out of its track. A **worn roller** can make the door loud and increase the force required to close it. Hinges and brackets should also be checked for looseness, but avoid removing any bracket connected to a spring or cable.

Check the threshold and **garage floor** for objects, raised sections, or buildup that could be mistaken for an obstruction. In some homes, an uneven concrete floor causes the bottom of the door to contact one side first. The opener may interpret this resistance as a safety issue.

The **weather seal** at the bottom of the door can also become rigid, swollen, or displaced. In Southern California, dust and grit can collect around the threshold and tracks. Los Angeles's dry conditions may increase the need for cleaning and appropriate lubrication, particularly in older garages or detached structures. Do not use heavy grease on tracks; it can attract more dirt. A technician can identify the correct lubricant for rollers, hinges, and bearings.

Broken Springs, Cables, or Balance Issues

A garage door depends on springs to offset much of its weight. A broken **torsion spring** is mounted above the door, while an **extension spring** is typically installed along the horizontal tracks. Either type can wear out or fail with age.

Indicators of a **failed torsion spring** may include a visible separation in the coil, a loud snapping sound, a door that feels unusually heavy, or an opener that lifts only part of the door. Extension springs may appear elongated, disconnected, or out of place. A door with a broken spring can close unevenly and reverse because the opener cannot handle the load.

Garage cables, also called **lifting cables**, transfer spring force to the door. Worn, loose, or derailed cables are a major warning. Do not handle a cable, remove a spring, or attempt to wind a torsion spring. The stored energy can cause severe injury.

A simple balance check is appropriate only when the spring and cables appear intact. With the door fully closed, disconnect the opener using the **emergency release** only if the door is stable and you can control it. Do not perform this test if the door is tilted, hanging, or visibly damaged. A properly balanced door should move freely by hand and remain near a midpoint when lifted carefully. If it falls or feels unusually heavy, stop and arrange professional service.

Secure Troubleshooting Before Calling for Garage door repair

Begin with the straightforward controls. Install the battery in the **garage door remote** if it works inconsistently, and check the **wall control panel**. Check whether the wall button is jammed, damaged, or showing an fault indicator. Confirm the opener's light and diagnostic LEDs are operating properly.

Examine the photo-eye sensors and remove obstructions from the opening. Ensure that their lights are constant when the door is closed and the opener has power. Sweep away visible debris from the threshold, but do not place an object under the door to keep it closed.

If the opener has no power, look at the household **circuit breaker** and the outlet. Reset a tripped breaker only once. If it trips again, keep the system off and call an electrician or garage door technician. Do not open the opener housing or handle electrical components unless qualified.

Use the **manual release cord** only when needed and only if the door is safely supported. Never disconnect a heavy or damaged door and leave it unsupported. Do not attempt changing force settings, travel limits, springs, cables, or track hardware as a do-it-yourself experiment. These adjustments affect the door's safety reversal and balance.

When to Call a Garage Door Repair Technician

Contact a professional for **garage door assistance** if the door remains open, reverses once you complete sensor cleaning, produces grinding or popping sounds, hangs unevenly, or has a broken spring or cable. You should also schedule help if the door is difficult to lift manually or the opener keeps shutting off.

Searches such as “ **garage door spring replacement near me**” can help you locate local providers, but review experience before hiring. A licensed technician should be able to examine the complete system, including the **garage door system**, springs, cables, rollers, tracks, hinges, sensors, and opener.

Professional help is especially important for older Los Angeles homes, detached garages, and converted garage spaces. Wiring may have been modified over the years, and an older door may not be compatible with a newer opener without further modifications. Accurate inspection of the door balance, wiring, mounting points, and opener compatibility prevents repeat failures.

Ask whether the company offers **same-day garage door repair**, emergency service, and written estimates. Same-day availability and travel charges can vary throughout Los Angeles County. A company serving Downtown Los Angeles may have varying response times and charges than one traveling to the San Fernando Valley, the Westside, or Long Beach.

Garage door repair Rates and Rates in Los Angeles

Garage door repair cost depends on the damaged component, the door's size and weight, accessibility, parts availability, and whether service is needed after normal business hours. **Garage door repair pricing** may include a diagnostic or **service call fee**, labor, replacement parts, disposal, and any emergency or travel charge.

Ask for a written estimate that separates labor from parts. Confirm whether the quote includes testing the safety reversal, balancing the door, adjusting travel limits, and removing old components. A low initial price may not include necessary replacement parts or additional work discovered during inspection.

How Much Does Garage door repair Cost?

Limited work, such as sensor cleaning, sensor alignment, lubrication, or tightening accessible hardware, is generally more affordable than replacing major components. The **garage door spring cost** changes according to spring type, door weight, cycle rating, and whether one or both springs should be replaced. Torsion spring work typically requires professional tools and careful balancing.

The **garage door opener installation cost** is based on the opener model, horsepower, rail configuration, electrical access, battery backup, remotes, and removal of the old unit. The total **labor cost** may be higher when the existing opener is incompatible with the door or when a detached garage requires additional wiring.

Because local conditions differ, a reputable Los Angeles company should inspect the door before giving a firm price. Ask about warranties on both labor and replacement parts. Verify whether the service call fee is credited toward approved repair work and whether evening, weekend, or emergency garage door repair has a separate rate.

Repair Versus Garage Door Replacement

Repair is often more economical when the frame, sections, tracks, and hardware are in good condition. Replacing a spring, roller, cable, sensor, or isolated **garage door panel** can maintain reliable operation without replacing the entire system.

Replacement work may be a better option if several panels are damaged, the door has widespread corrosion, the tracks are badly bent, or the opener and door are both outdated. Compare the **garage door replacement cost**

with the expected cost of ongoing repairs. Insulation, wind resistance, design, and long-term maintenance should also be considered.

Many homeowners commonly ask about **2 car garage door replacement cost** or **two car garage door replacement cost**. A two-car door is larger and heavier, so its price can differ substantially from a single-car door. The final estimate depends on the material, insulation, windows, hardware, removal, installation, and local labor. A panel replacement may be appropriate when damage is limited, but a full replacement can be more cost-effective when several sections or the supporting hardware are failing.

Searching for Garage Door Repair Close to Me in Los Angeles

For **garage door repair near me** in Los Angeles, select a **certified garage door technician** with proper insurance, complete business information, and nearby reviews. Request a written diagnosis, itemized estimate, warranty terms, and projected arrival window. Verify that the technician is authorized to perform spring work and that the company will test the safety reversal after completing repairs.

Response times and travel fees change across **Los Angeles County**. Downtown Los Angeles, the San Fernando Valley, the Westside, and Long Beach may have different technician availability, traffic delays, and service-area charges. If you need **today's garage door repair**, ask whether same-day service is assured or simply offered when a technician is available.

Southern California's dust, grit, and dry conditions can influence photo-eye sensors, tracks, rollers, hinges, and lubrication. A reputable local company should account for these conditions rather than replacing parts without checking the underlying cause. Many Los Angeles properties also have detached garages or converted garage spaces, where wiring, framing, and opener compatibility require careful inspection.

Preventing the Door From Reversing

Routine **garage door maintenance** helps avoid unplanned reversals. Keep the sensor lenses free of dirt and make sure the sensor brackets are properly aligned. Check the door for unexpected gaps, noise, vibration, cable slack, and uneven movement. Clean debris from the threshold and track area without forcing debris into the rollers.

Use suitable **oiling** on hinges, bearings, and roller surfaces in line with the manufacturer's instructions. Refrain from heavily oiling the tracks because grease can collect dust and create more resistance. In Los Angeles, regular cleaning is particularly useful during dusty, dry conditions.

Never alter **force adjustments** simply to get a malfunctioning door to close. Too much force can affect the opener's safety reversal. Travel limits should be set so the door comes down firmly against the floor without compressing the weather seal. A technician can handle these settings while verifying balance and mechanical resistance.

Arrange a **preventative checkup** when the door becomes noisy, slow, uneven, or difficult to operate. Preventive maintenance is more convenient than waiting for a spring, roller, cable, or opener to break down entirely. Check the safety reversal only as directed by the opener manufacturer and do not let children or pets near a moving door.

Questions We Hear Often

What makes my garage door close all the way and then open again?

The opener may be detecting resistance from a dusty sensor, misaligned track, worn roller, stiff weather seal, or incorrect travel limit. A damaged or broken **door spring** can also prevent the door from closing properly. Clean and inspect the safety sensors first, but call for garage door repair if the door is heavy, uneven, noisy, or still reverses.

How can I fix garage door safety sensors that are misaligned?

Clear the area between the sensors, wipe both lenses, and check that the brackets point toward one another at the same height. Look for a blinking sensor light, loose mounting hardware, or damaged sensor wiring. Do not bypass the **safety sensors**. If the lights remain unstable after proper adjustment, a technician should test the wiring and replace defective components.

What is the cost of garage door repair in Los Angeles?

Garage door service pricing varies by part, labor, door size, urgency, and location. The estimate may include a service call fee, labor, and replacement parts. Spring work and opener replacement generally cost more than sensor alignment or minor adjustment. Ask a Los Angeles provider for a written, itemized quote and confirm warranty coverage before authorizing work.

Should I repair a garage door panel or replace the entire door?

Repairing a single **door panel** may be practical when the damage is limited and the remaining sections and hardware are sound. Full replacement may **garage door installation** offer better value when several panels, tracks, springs, or the opener are deteriorated. Compare the repair estimate with the garage door replacement cost, including installation, removal, insulation, and hardware.

When should I call for garage door spring replacement near me?

Call immediately if you see a broken torsion spring or extension spring, a loose or frayed cable, a crooked door, or a door that suddenly becomes very heavy. Do not attempt spring repair or replacement yourself. Search for **local garage door spring replacement** and verify licensing, insurance, experience, written pricing, and warranty terms before choosing a provider.